


## Technical data sheet

Article number:  
117-05008

T50RDH



<b>Product Group</b>	Cable ties for parallel routing
<b>Product Family</b>	DH-Series
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Colour</b>	Natural (NA)
<b>Application Tool</b>	ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP
<b>Bundle Ø max.</b>	38.0 mm
<b>Bundle Ø min.</b>	1.6 mm
<b>Flammability</b>	UL 94 V2
<b>Halogen-free</b>	Yes
<b>Length (L)</b>	210.82 mm
<b>Min.Tensile Strength</b>	225 N
<b>Operating Temperature</b>	-40 °C to +85 °C
<b>Package Content packed in</b>	pack
<b>Pack Cont.</b>	1000 pcs.
<b>Releasable Closure (Yes/No)</b>	No
<b>Specifications</b>	UL
<b>Toothing (Serration)</b>	Inside Serrated
<b>UL-File Number</b>	E64139
<b>Variant</b>	Inside Serrated
<b>Width (W)</b>	4.7 mm

