

Materiale datablad

Varenummer
117-05250

T50I



Produktgruppe	Kabelbindere til temperaturer op til + 105°C (varmestabiliseret)
Produktserie	T serieni PA66HS sort
Materiale	Polyamid 6.6, varmestabiliseret (PA66HS)
Farve	Sort (BK)
Anbefalet monteringsværktøj	ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP
Antal pr.	pose
Bredde (W)	4,6 mm
Bundtdiameter max.	85,0 mm
Bundtdiameter min.	1,5 mm
Driftstemperatur	-40 °C til +105 °C, (+145 °C, 500 h)
Flammehæmmende egenskab	Iht. UL94 V2
Fortanding	Indvendig fortanding
Genoplukkelig	Nej
Halogenfri	Ja
Længde (L)	300 mm
Min. trækstyrke	225 N
Pakkeindhold	100 Stk.
Specifikation	csa-C22.2 no. 62275, IEC 60092 series, VG U48/04102
UL fil nummer	E64963
UV resistent ASTM D6779	Nej
Variant	Indvendig fortanding
Vægt	0,002118 kg

