

Technical data sheet

Article number:

Width (W)

118-00128 T50MOS

| Product Group Cable ties for thin-walled bundles Product Family OS-Series Material Polyamide 6.6, UV-resistant (PA66W) Colour Black (BK) Application Tool MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7iSP Bundle Ø max. 66.0 mm Bundle Ø min. 1.6 mm Flammability UL 94 V2 Halogen-free Yes Height (H) 1.3 mm Length (L) 245 mm Min.Tensile Strength 225 N Operating Temperature -40 °C to +85 °C Package Content packed in bag Pack Cont. 100 pcs. | L | |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|---------------------------------------------------------------|
| Product Family OS-Series Material Polyamide 6.6, UV-resistant (PA66W) Colour Black (BK) Application Tool MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7iSP Bundle Ø max. 66.0 mm Bundle Ø min. 1.6 mm Flammability UL 94 V2 Halogen-free Yes Height (H) 1.3 mm Length (L) 245 mm Min.Tensile Strength 225 N Operating Temperature -40 °C to +85 °C Package Content packed in bag | | |
| Product Family OS-Series Material Polyamide 6.6, UV-resistant (PA66W) Colour Black (BK) Application Tool MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7iSP Bundle Ø max. 66.0 mm Bundle Ø min. 1.6 mm Flammability UL 94 V2 Halogen-free Yes Height (H) 1.3 mm Length (L) 245 mm Min.Tensile Strength 225 N Operating Temperature -40 °C to +85 °C Package Content packed in bag | | |
| MaterialPolyamide 6.6, UV-resistant (PA66W)ColourBlack (BK)Application ToolMK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7iSPBundle Ø max.66.0 mmBundle Ø min.1.6 mmFlammabilityUL 94 V2Halogen-freeYesHeight (H)1.3 mmLength (L)245 mmMin.Tensile Strength225 NOperating Temperature-40 °C to +85 °CPackage Content packed inbag | Product Group | Cable ties for thin-walled bundles |
| ColourBlack (BK)Application ToolMK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7iSPBundle Ø max.66.0 mmBundle Ø min.1.6 mmFlammabilityUL 94 V2Halogen-freeYesHeight (H)1.3 mmLength (L)245 mmMin.Tensile Strength225 NOperating Temperature-40 °C to +85 °CPackage Content packed inbag | Product Family | OS-Series |
| Application Tool MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7iSP Bundle Ø max. 66.0 mm Bundle Ø min. 1.6 mm Flammability UL 94 V2 Halogen-free Yes Height (H) 1.3 mm Length (L) 245 mm Min.Tensile Strength 225 N Operating Temperature -40 °C to +85 °C Package Content packed in bag | Material | Polyamide 6.6, UV-resistant (PA66W) |
| Bundle Ø max. 66.0 mm Bundle Ø min. 1.6 mm Flammability UL 94 V2 Halogen-free Yes Height (H) 1.3 mm Length (L) 245 mm Min.Tensile Strength 225 N Operating Temperature -40 °C to +85 °C Package Content packed in bag | Colour | Black (BK) |
| Bundle Ø max. 66.0 mm Bundle Ø min. 1.6 mm Flammability UL 94 V2 Halogen-free Yes Height (H) 1.3 mm Length (L) 245 mm Min.Tensile Strength 225 N Operating Temperature -40 °C to +85 °C Package Content packed in bag | | |
| Bundle Ø min.1.6 mmFlammabilityUL 94 V2Halogen-freeYesHeight (H)1.3 mmLength (L)245 mmMin.Tensile Strength225 NOperating Temperature-40 °C to +85 °CPackage Content packed inbag | Application Tool | MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7iSP |
| FlammabilityUL 94 V2Halogen-freeYesHeight (H)1.3 mmLength (L)245 mmMin.Tensile Strength225 NOperating Temperature-40 °C to +85 °CPackage Content packed inbag | Bundle Ø max. | 66.0 mm |
| Halogen-freeYesHeight (H)1.3 mmLength (L)245 mmMin.Tensile Strength225 NOperating Temperature-40 °C to +85 °CPackage Content packed inbag | Bundle Ø min. | 1.6 mm |
| Height (H) 1.3 mm Length (L) 245 mm Min.Tensile Strength 225 N Operating Temperature -40 °C to +85 °C Package Content packed in bag | Flammability | UL 94 V2 |
| Length (L)245 mmMin.Tensile Strength225 NOperating Temperature-40 °C to +85 °CPackage Content packed inbag | Halogen-free | Yes |
| Min.Tensile Strength225 NOperating Temperature-40 °C to +85 °CPackage Content packed inbag | Height (H) | 1.3 mm |
| Operating Temperature -40 °C to +85 °C Package Content packed in bag | Length (L) | 245 mm |
| Package Content packed in bag | Min.Tensile Strength | 225 N |
| | Operating Temperature | -40 °C to +85 °C |
| Pack Cont.100 pcs. | Package Content packed in | bag |
| | Pack Cont. | 100 pcs. |
| Releasable Closure (Yes/No) No | Releasable Closure (Yes/No) | No |
| Specifications EN 45545-2 | Specifications | EN 45545-2 |
| Thickness (T) 1.3 mm | Thickness (T) | 1.3 mm |
| Toothing (Serration) Outside Serrated | Toothing (Serration) | Outside Serrated |
| Variant Outside Serrated | Variant | Outside Serrated |
| Weight/Unit 0.001646 kg | Weight/Unit | 0.001646 kg |

HF RoHS

4.6 mm

EN 45545-2