


## Technical data sheet

Article number:  
121-83360

KR8/33



|                             |                                       |
|-----------------------------|---------------------------------------|
| Product Group               | Cable tie locked by glass fibre pin   |
| Product Family              | KR-Series, 1-Piece                    |
| Material                    | Polyamide 6.6, UV-stabilised (PA66UV) |
| Colour                      | Black (BK)                            |
|                             |                                       |
| Application Range           | Outdoor Use                           |
| Application Tool            | KR6/8, KR8PNSE, EVO-KR                |
| Bundle Ø max.               | 86.0 mm                               |
| Bundle Ø min.               | 8.0 mm                                |
| Fixation Method             | Cable Tie                             |
| Flammability                | UL 94 V2                              |
| Length (L)                  | 337.0 mm                              |
| Min.Tensile Strength        | 785 N                                 |
| Operating Temperature       | -40 °C to +85 °C                      |
| Package Content packed in   | pack                                  |
| Pack Cont.                  | 50 pcs.                               |
| Releasable Closure (Yes/No) | No                                    |
| Specifications              | IEC 62275:2006                        |
| Thickness (T)               | 2.3 mm                                |
| Toothing (Serration)        | Not Serrated                          |
| Variant                     | Not Serrated                          |
| Weight/Unit                 | 0.004387 kg                           |
| Width (W)                   | 8.0 mm                                |

RoHS

