

## Technical data sheet

Article number:  
126-00173

**T50SL7**

|                               |                                                                                                                        |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------|
| Product Group                 | 1-Piece Fixing Ties with Arrowhead, with Wings                                                                         |
| Product Family                | for round holes                                                                                                        |
| Material                      | Polyamide 6.6, heat stabilised (PA66HS)                                                                                |
| Colour                        | Black (BK)                                                                                                             |
| Application Tool              | ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP |
| Bundle Ø max.                 | 34.0 mm                                                                                                                |
| Bundle Ø min.                 | 1.5 mm                                                                                                                 |
| Fixation Method               | arrowhead                                                                                                              |
| for Hole Ø (FH)               | 6.9 - 7.1 mm                                                                                                           |
| Height (H)                    | 10.0 mm                                                                                                                |
| Length (L)                    | 165 mm                                                                                                                 |
| Min.Tensile Strength          | 225 N                                                                                                                  |
| Package Content packed in     | bag                                                                                                                    |
| Pack Cont.                    | 500 pcs.                                                                                                               |
| Panel Thickness               | 2.5 mm                                                                                                                 |
| Panel Thickness max.          | 0.8 – 2.5 mm                                                                                                           |
| Panel Thickness min. (metric) | 0.8 mm                                                                                                                 |
| ROHS compliant                | Yes                                                                                                                    |
| Thickness (T)                 | 1.2 mm                                                                                                                 |
| Variant                       | Inside Serrated                                                                                                        |
| Width (W)                     | 4.6 mm                                                                                                                 |

