

## Technical data sheet

**Article number:**  
**126-00183**

**PT2ASFT6.5PT0.7-1.5-E**

|                                      |  |
|--------------------------------------|--|
| <b>Product Group</b>                 | 1-Piece Fixing Ties with Arrowhead, with Disc, for round holes |
| <b>Product Family</b>                | With arrowhead, with disc, for round holes                     |
| <b>Material</b>                      | Polyetheretherketone (PEEK)                                    |
| <b>Colour</b>                        | Beige (BGE)  |
| <b>Application Tool</b>              | MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7iSP  |
| <b>Bundle Ø max.</b>                 | 20 mm  |
| <b>Bundle Ø min.</b>                 | 4 mm   |
| <b>Fixation Method</b>               | arrowhead  |
| <b>Flammability</b>                  | UL 94 V0 (3 mm)  |
| <b>for Hole Ø (FH)</b>               | 6.3 - 6.7 mm   |
| <b>Length (L)</b>                    | 112.7 mm   |
| <b>Min.Tensile Strength</b>          | 230 N  |
| <b>Operating Temperature</b>         | -55 °C to +240 °C  |
| <b>Package Content packed in</b>     | bag  |
| <b>Pack Cont.</b>                    | 9000 pcs.  |
| <b>Panel Thickness</b>               | 1.5 mm   |
| <b>Panel Thickness max.</b>          | 0.7 – 1.5 mm   |
| <b>Panel Thickness min. (metric)</b> | 0.7 mm   |
| <b>ROHS compliant</b>                | Yes  |
| <b>Variant</b>                       | Outside Serrated   |
| <b>Width (W)</b>                     | 3.4 mm   |

