

## Technical data sheet

Article number:  
126-00188

**T50SL7**

|                                      |                                                                                                                        |
|--------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| <b>Product Group</b>                 | 1-Piece Fixing Ties with Arrowhead, with Wings                                                                         |
| <b>Product Family</b>                | for round holes                                                                                                        |
| <b>Material</b>                      | Polyamide 6.6, heat stabilised (PA66HS)                                                                                |
| <b>Colour</b>                        | Natural (NA)                                                                                                           |
| <b>Application Tool</b>              | ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP |
| <b>Bundle Ø max.</b>                 | 34.0 mm                                                                                                                |
| <b>Bundle Ø min.</b>                 | 1.5 mm                                                                                                                 |
| <b>Fixation Method</b>               | arrowhead                                                                                                              |
| <b>for Hole Ø (FH)</b>               | 6.9 - 7.1 mm                                                                                                           |
| <b>Height (H)</b>                    | 10.0 mm                                                                                                                |
| <b>Length (L)</b>                    | 165 mm                                                                                                                 |
| <b>Min.Tensile Strength</b>          | 225 N                                                                                                                  |
| <b>Package Content packed in</b>     | bag                                                                                                                    |
| <b>Pack Cont.</b>                    | 500 pcs.                                                                                                               |
| <b>Panel Thickness</b>               | 2.5 mm                                                                                                                 |
| <b>Panel Thickness max.</b>          | 0.8 – 2.5 mm                                                                                                           |
| <b>Panel Thickness min. (metric)</b> | 0.8 mm                                                                                                                 |
| <b>ROHS compliant</b>                | Yes                                                                                                                    |
| <b>Thickness (T)</b>                 | 1.2 mm                                                                                                                 |
| <b>Variant</b>                       | Inside Serrated                                                                                                        |
| <b>Width (W)</b>                     | 4.6 mm                                                                                                                 |

