

## Technical data sheet

**Article number:**  
**126-00205**

**T8RWPM3.5**

<b>Product Group</b>	Suitable for routing small-diameter cables in close proximity to a circuit board or for attaching cables to the reverse side of a chassis in limited space.
<b>Product Family</b>	Applicable to the smallest panel hole $\phi 3.5\text{mm}$ Ideal for small diameter cables.
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Colour</b>	Natural (NA)
<b>Application Tool</b>	MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7iSP
<b>Bundle Ø max.</b>	15 mm
<b>Bundle Ø min.</b>	1.0 mm
<b>Fixation Method</b>	arrowhead
<b>Flammability</b>	UL 94 V2
<b>for Hole Ø (FH)</b>	3.4 - 3.6 mm
<b>Length (L)</b>	81 mm
<b>Min.Tensile Strength</b>	36 N
<b>Operating Temperature</b>	-40 °C to +85 °C
<b>Package Content packed in</b>	bag
<b>Pack Cont.</b>	500 pcs.
<b>Panel Thickness</b>	1.6 mm
<b>Panel Thickness max.</b>	0.4 – 1.6 mm
<b>Panel Thickness min. (metric)</b>	0.4 mm
<b>ROHS compliant</b>	Yes
<b>Specifications</b>	ANSI/UL 1565, ANSI/UL 62275
<b>Thickness (T)</b>	0.9
<b>UL-File Number</b>	E64962
<b>Width (W)</b>	1.7 mm

