

Technical data sheet

Article number:
126-00206

T8RWPM3.5

Product Group	Suitable for routing small-diameter cables in close proximity to a circuit board or for attaching cables to the reverse side of a chassis in limited space.
Product Family	Applicable to the smallest panel hole $\phi 3.5\text{mm}$ Ideal for small diameter cables.
Material	Polyamide 6.6 V0 (PA66V0)
Colour	White (WH)
Application Tool	MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7iSP
Bundle Ø max.	15 mm
Bundle Ø min.	1.0 mm
Fixation Method	arrowhead
Flammability	UL 94 V0
for Hole Ø (FH)	3.4 - 3.6 mm
Length (L)	81 mm
Min.Tensile Strength	36 N
Operating Temperature	-40 °C to +105 °C
Package Content packed in	bag
Pack Cont.	500 pcs.
Panel Thickness	1.6 mm
Panel Thickness max.	0.4 – 1.6 mm
Panel Thickness min. (metric)	0.4 mm
ROHS compliant	Yes
Specifications	ANSI/UL 1565, ANSI/UL 62275
Thickness (T)	0.9
UL-File Number	E64962
Width (W)	1.7 mm

