


## Technical data sheet

Article number:  
126-01004

**T50RSF(U)**



|                                      |                                                               |
|--------------------------------------|---------------------------------------------------------------|
| <b>Product Group</b>                 | 1-Piece Fixing Ties with Arrowhead                            |
| <b>Product Family</b>                | without wings and disc, for round holes                       |
| <b>Material</b>                      | Polyamide 6.6, heat stabilised (PA66HS)                       |
| <b>Colour</b>                        | Black (BK)                                                    |
| <b>Application Tool</b>              | MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7iSP |
| <b>Bundle Ø max.</b>                 | 44.5 mm                                                       |
| <b>Bundle Ø min.</b>                 | 1.6 mm                                                        |
| <b>CE Certification</b>              | Yes                                                           |
| <b>Fixation Method</b>               | arrowhead                                                     |
| <b>Flammability</b>                  | UL 94 V2                                                      |
| <b>for Hole Ø (FH)</b>               | 6.4 - 7.1 mm                                                  |
| <b>Height (H)</b>                    | 7.50 mm                                                       |
| <b>Length (L)</b>                    | 210.82 mm                                                     |
| <b>Min.Tensile Strength</b>          | 225 N                                                         |
| <b>Operating Temperature</b>         | -40 °C to +125 °C                                             |
| <b>Package Content packed in</b>     | pack                                                          |
| <b>Pack Cont.</b>                    | 1000 pcs.                                                     |
| <b>Panel Thickness</b>               | 3.56 mm                                                       |
| <b>Panel Thickness max.</b>          | 1.0 - 3.56 mm                                                 |
| <b>Panel Thickness min. (metric)</b> | 1.0 mm                                                        |
| <b>ROHS compliant</b>                | Yes                                                           |
| <b>Specifications</b>                | UL-ZODZ2.E64139                                               |
| <b>Thickness (T)</b>                 | 1.2 mm                                                        |
| <b>UL-File Number</b>                | E64139                                                        |
| <b>Variant</b>                       | Inside Serrated                                               |
| <b>Width (W)</b>                     | 4.7 mm                                                        |

