

## **Technical data sheet**

Panel Thickness min. (metric)

**ROHS** compliant

Thickness (T)

Variant

Width (W)

**Article number:** 

126-02300 T50SST5

•	L	•
		Tw/
		<u></u>

Product Group	1-piece fixing ties with arrowhead, with disc	
Product Family	for round holes	
Material	Polyamide 6.6 (PA66)	
Colour	Natural (NA)	
Application Tool	ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP	
Bundle Ø max.	31.0 mm	
Bundle Ø min.	1.5 mm	
CE Certification	No	
Fixation Method	arrowhead	
Flammability	UL 94 V2	
for Hole Ø (FH)	6.1 - 6.5 mm	
Length (L)	170.0 mm	
Min.Tensile Strength	225 N	
Operating Temperature	-40 °C to +85 °C	
Package Content packed in	pack	
Pack Cont.	1000 pcs.	
Panel Thickness	1.5 mm	
Panel Thickness max.	0.7 - 1.5 mm	



Inside Serrated

0.7 mm

1.2 mm

4.6 mm

Yes