


Technical data sheet

Article number: 126-03504

Product Group

T50RTM25E



1 Todact Group	I piece fixing des with in dee, with dise, for round holes
Product Family	Fir tree parts FT6
Material	Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
Colour	Grey (GY)
Application Tool	ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP
Bundle Ø max.	50.8 mm
Bundle Ø min.	1.6 mm
CE Certification	No
Fixation Method	Fir tree for round holes
Flammability	UL 94 HB
for Hole Ø (FH)	6.25 - 7.0 mm
Height (H)	1.3 mm
Length (L)	203.2 mm
Min.Tensile Strength	222 N
Operating Temperature	-40 °C to +105 °C
Package Content packed in	pack
Pack Cont.	1000 pcs.
Panel Thickness	13.9 mm
Panel Thickness max.	2.3 - 13.9 mm
Panel Thickness min. (metric)	2.3 mm
ROHS compliant	Yes
Thickness (T)	1.3 mm
Variant	Inside Serrated
Width (W)	4.7 mm

1-piece fixing ties with fir tree, with disc, for round holes

