

## Technical data sheet

Article number:  
131-75019

RT250R

|                             |                                                 |
|-----------------------------|-------------------------------------------------|
| Product Group               | Cable ties inside serrated with tuckaway        |
| Product Family              | RT250-Series up to 1115 N loop tensile strength |
| Material                    | Polyamide 6.6 (PA66)                            |
| Colour                      | Natural (NA)                                    |
| Application Range           | Indoor Use                                      |
| Bundle Ø max.               | 125.0 mm                                        |
| Bundle Ø min.               | 12.0 mm                                         |
| Flammability                | UL 94 V2                                        |
| Length (L)                  | 515.0 mm                                        |
| Min.Tensile Strength        | 1115 N                                          |
| Operating Temperature       | -40 °C to +85 °C                                |
| Package Content packed in   | pack                                            |
| Pack Cont.                  | 25 pcs.                                         |
| Releasable Closure (Yes/No) | Yes                                             |
| Specifications              | UL-ZODZ2.E64139                                 |
| Thickness (T)               | 1.9 mm                                          |
| UL-File Number              | E64139                                          |
| Variant                     | Inside Serrated                                 |
| Weight/Unit                 | 0.0122 kg                                       |
| Width (W)                   | 12.5 mm                                         |

