

## Technical data sheet

Article number:  
133-03178

**PC5AH6.5**

|                                      |   |
|--------------------------------------|---|
| <b>Product Group</b>                 | Fixing elements for tubes and harnesses                                   |
| <b>Material</b>                      | Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV) |
| <b>Colour</b>                        | Black (BK)  |
| <b>Bundle Ø max.</b>                 | 4.9 mm  |
| <b>Bundle Ø min.</b>                 | 4.5 mm  |
| <b>CE Certification</b>              | No  |
| <b>Fixation Method</b>               | arrowhead   |
| <b>Flammability</b>                  | UL 94 HB  |
| <b>for Hole Ø (FH)</b>               | 6.1 - 6.9 mm, 6.35 mm (hexagonal)   |
| <b>Height (H)</b>                    | 21.5 mm   |
| <b>Length (L)</b>                    | 17.0 mm   |
| <b>Operating Temperature</b>         | -40 °C to +105 °C   |
| <b>Package Content packed in</b>     | pack  |
| <b>Pack Cont.</b>                    | 4000 pcs.   |
| <b>Panel Thickness</b>               | 1.6 mm  |
| <b>Panel Thickness max.</b>          | 1.2 - 1.6 mm  |
| <b>Panel Thickness min. (metric)</b> | 1.2 mm  |
| <b>ROHS compliant</b>                | Yes   |
| <b>Width (W)</b>                     | 10.0 mm   |

**RoHS** 