


Technical data sheet

Article number:
148-90031

HECE-3



Product Group	Connectors - For Solid Wires
Product Family	HelaCon Easy
Material	Polyamide 6.6 (PA66)
Colour	Grey (GY)
Depth (D)	0.78 "
Depth D (metric)	19.7 mm
Flammability	UL 94 V2
Height (H)	0.37 "
Height H (metric)	9.5 mm
Length (L)	19.7 mm
Length L (imperial)	0.78 "
Material Housing	Polyamide (PA)
Material Plated Brass	Brass Tinned (MET)
Material Spring Plate	Stainless Steel (SS)
Max Current	24 A
Max Voltage	450 V
Number of Conductors	3
Operating Temperature	-30 °C to +110 °C (VDE), -30 °C to +105 °C, -30 °C to +105 °C
Specifications	FIMKO, ENEC, CEBEC, UL ANSI/UL 486-C, UL ANSI/UL 486-B, UL ANSI/UL 486-A, KEMA KEUR EN 60998-2-2:2004, KEMA KEUR 60998-1:2004, VDE DIN EN 60998-2-2:2005-03
Stripping Length	11 mm
Stripping Length (Imperial)	0.43 "
Width (W)	13.5 mm
Width (W) (imperial)	0.53 "
Wire Range (cULus)	12 - 22 AWG solid
Wire Range (VDE)	1.0 - 2.5 mm² solid

