


## **Technical data sheet**

Article number: 150-31096

**Product Group** 

T80IFT6LG



1 Todact Group	2 Freee Fixing fies with the free, with bise, for Round Froies
Product Family	Fir tree parts FT6
Material	Polyamide 6.6, heat stabilised (PA66HS), Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP
Bundle Ø max.	75.0 mm
Bundle Ø min.	5.0 mm
Cable Tie	Polyamide 6.6, heat stabilised (PA66HS)
Fixation Method	Fir Tree
Flammability	UL 94 HB
Foot Part	Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
for Hole Ø (FH)	6.5 - 7.0 mm
Height (H)	1.2 mm
Length (L)	305.0 mm
Length (L2)	11.6 mm
Min.Tensile Strength	355 N
Operating Temperature	-40 °C to +105 °C
Package Content packed in	pcs.
Pack Cont.	500 pcs.
Panel Thickness	6.0 mm
Panel Thickness min. (metric)	0.75 mm
ROHS compliant	Yes
Thickness (T)	1.2 mm
Variant	Inside Serrated
Width (W)	4.7 mm

2-Piece Fixing Ties with Fir Tree, with Disc, for Round Holes

