

## Technical data sheet

Article number:  
150-31098

**T50RFT6LG**



|                                      |                                                                                                                        |
|--------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| <b>Product Group</b>                 | 2-Piece Fixing Ties with Fir Tree, with Disc, for Round Holes                                                          |
| <b>Product Family</b>                | Fir tree parts FT6                                                                                                     |
| <b>Material</b>                      | Polyamide 4.6 (PA46)                                                                                                   |
| <b>Colour</b>                        | Grey (GY)                                                                                                              |
| <b>Application Tool</b>              | ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP |
| <b>Bundle Ø max.</b>                 | 45.0 mm                                                                                                                |
| <b>Bundle Ø min.</b>                 | 5.0 mm                                                                                                                 |
| <b>CE Certification</b>              | No                                                                                                                     |
| <b>Fixation Method</b>               | Fir tree for round holes                                                                                               |
| <b>for Hole Ø (FH)</b>               | 6.5 - 7.0 mm                                                                                                           |
| <b>Height (H)</b>                    | 1.2 mm                                                                                                                 |
| <b>Length (L)</b>                    | 200.0 mm                                                                                                               |
| <b>Length (L2)</b>                   | 11.6 mm                                                                                                                |
| <b>Min.Tensile Strength</b>          | 222 N                                                                                                                  |
| <b>Operating Temperature</b>         | -40 °C to +150 °C                                                                                                      |
| <b>Package Content packed in</b>     | pack                                                                                                                   |
| <b>Pack Cont.</b>                    | 500 pcs.                                                                                                               |
| <b>Panel Thickness</b>               | 6.0 mm                                                                                                                 |
| <b>Panel Thickness max.</b>          | 0.75 - 6.0 mm                                                                                                          |
| <b>Panel Thickness min. (metric)</b> | 0.75 mm                                                                                                                |
| <b>ROHS compliant</b>                | Yes                                                                                                                    |
| <b>Variant</b>                       | Inside Serrated                                                                                                        |
| <b>Width (W)</b>                     | 4.6 mm                                                                                                                 |

