Technical data sheet

Product Family 2-p Material Poly Stat	iece fixing ties with arrowhead, with disc iece fixing ties with arrowhead, with disc, for round holes yamide 6.6, heat stabilised (PA66HS), Polyamide 6.6, high impact modified, heat
Material Poly Stat	<u> </u>
Staterial staterial state	vamide 6.6. heat stabilised (PA66HS). Polvamide 6.6. high impact modified, heat
Pro	bilised (PA66HIRHS)
Pro	ck (BK)
Pro	
	Cut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, D7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP
Bundle Ø max.45.1	0 mm
Bundle Ø min.4.0	mm
Fixation Method arrow	owhead
for Hole Ø (FH) 6.3	x 12.2 mm
Height (H) 1.2	mm
_ength (L) 202	2 mm
Vin.Tensile Strength222	2 N
Package Content packed in bag	
Pack Cont. 500) pcs.
Panel Thickness 3.0	mm
Panel Thickness min. (metric) 0.6	mm
ROHS compliant Yes	
/ariant Insi	
Vidth (W) 4.6	ide Serrated



Technical changes and errors reserved. It's up to the customer to check the suitability for a specific application by means of tests.