

## Technical data sheet

Article number:  
150-37791

**T50ROSSFT6.5-16-3**

<b>Product Group</b>	2-piece fixing ties with arrowhead, with disc
<b>Product Family</b>	2-Piece Fixing Ties with Arrowhead, with Disc, for round holes
<b>Material</b>	Polyamide 6.6, heat stabilised (PA66HS), Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
<b>Colour</b>	Black (BK)
<b>Application Tool</b>	ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP
<b>Bundle Ø max.</b>	45.0 mm
<b>Bundle Ø min.</b>	5.0 mm
<b>Cable Tie</b>	Polyamide 6.6, heat stabilised (PA66HS)
<b>CE Certification</b>	No
<b>Fixation Method</b>	arrowhead
<b>Flammability</b>	UL 94 HB
<b>Foot Part</b>	Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
<b>for Hole Ø (FH)</b>	6.3 - 6.7 mm
<b>Height (H)</b>	1.3 mm
<b>Length (L)</b>	200 mm
<b>Length (L2)</b>	11.6 mm
<b>Min.Tensile Strength</b>	225 N
<b>Operating Temperature</b>	-40 °C to +105 °C
<b>Package Content packed in</b>	pack
<b>Pack Cont.</b>	500 pcs.
<b>Panel Thickness</b>	3.5 mm
<b>Panel Thickness max.</b>	2.5 - 3.5 mm
<b>Panel Thickness min. (metric)</b>	2.5 mm
<b>ROHS compliant</b>	Yes
<b>Variant</b>	Outside Serrated
<b>Width (W)</b>	4.6 mm

