

## Technical data sheet

Article number:  
150-52690

T30RFT6SD



<b>Product Group</b>	2-Piece Fixing Ties with Fir Tree, with Disc, for Round Holes
<b>Product Family</b>	Fir tree parts FT6
<b>Material</b>	Polyamide 6.6, heat stabilised (PA66HS), Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
<b>Colour</b>	Black (BK)
<b>Application Tool</b>	MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP
<b>Bundle Ø max.</b>	35.0 mm
<b>Bundle Ø min.</b>	1.5 mm
<b>Cable Tie</b>	Polyamide 6.6, heat stabilised (PA66HS)
<b>Fixation Method</b>	Fir Tree
<b>Flammability</b>	UL 94 HB
<b>Foot Part</b>	Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
<b>for Hole Ø (FH)</b>	6.4 - 7.1 mm
<b>Height (H)</b>	1.1 mm
<b>Length (L)</b>	150.0 mm
<b>Length (L2)</b>	11.6 mm
<b>Min.Tensile Strength</b>	135 N
<b>Operating Temperature</b>	-40 °C to +105 °C
<b>Package Content packed in</b>	bag
<b>Pack Cont.</b>	500 pcs.
<b>Panel Thickness</b>	3.0 mm
<b>Panel Thickness min. (metric)</b>	0.75 mm
<b>ROHS compliant</b>	Yes
<b>Thickness (T)</b>	1.1 mm
<b>Variant</b>	Inside Serrated
<b>Width (W)</b>	3.5 mm

