Technical data sheet

Product Group 2-piece fixing ties for weld studs, for parallel routing Product Family 2-piece fixing ties for weld studs, for parallel routing Material Polyamide 6.6, heat stabilised (PA66HS), Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS) Colour Black (BK) Application Tool MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7iSP Bundle Ø max. 35.0 mm Bundle Ø min. 2.0 mm Cable Tie Polyamide 6.6, heat stabilised (PA66HS) Flammability UL 94 HB Foot Part Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS) Height (H) 1.2 mm Lenoth (L) 150 mm	Article number: 150-56193	T50SDSBS5
Material Polyamide 6.6, heat stabilised (PA66HS), Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS) Colour Black (BK) Application Tool MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7iSP Bundle Ø max. 35.0 mm Bundle Ø min. 2.0 mm Cable Tie Polyamide 6.6, heat stabilised (PA66HS) Flammability UL 94 HB Foot Part Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS) Height (H) 1.2 mm	Product Group	2-piece fixing ties for weld studs, for parallel routing
Material stabilised (PA66HIRHS) Colour Black (BK) Application Tool MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7iSP Bundle Ø max. 35.0 mm Bundle Ø min. 2.0 mm Cable Tie Polyamide 6.6, heat stabilised (PA66HIS) Flammability UL 94 HB Foot Part Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS) Height (H) 1.2 mm	Product Family	2-piece fixing ties for weld studs, for parallel routing
Application Tool MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7iSP Bundle Ø max. 35.0 mm Bundle Ø min. 2.0 mm Cable Tie Polyamide 6.6, heat stabilised (PA66HS) Flammability UL 94 HB Foot Part Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS) Height (H) 1.2 mm	Material	
Bundle Ø max.35.0 mmBundle Ø min.2.0 mmCable TiePolyamide 6.6, heat stabilised (PA66HS)FlammabilityUL 94 HBFoot PartPolyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)Height (H)1.2 mm	Colour	Black (BK)
Bundle Ø max.35.0 mmBundle Ø min.2.0 mmCable TiePolyamide 6.6, heat stabilised (PA66HS)FlammabilityUL 94 HBFoot PartPolyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)Height (H)1.2 mm		
Bundle Ø min. 2.0 mm Cable Tie Polyamide 6.6, heat stabilised (PA66HS) Flammability UL 94 HB Foot Part Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS) Height (H) 1.2 mm	Application Tool	MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7iSP
Cable TiePolyamide 6.6, heat stabilised (PA66HS)FlammabilityUL 94 HBFoot PartPolyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)Height (H)1.2 mm	Bundle Ø max.	35.0 mm
Flammability UL 94 HB Foot Part Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS) Height (H) 1.2 mm	Bundle Ø min.	2.0 mm
Foot PartPolyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)Height (H)1.2 mm	Cable Tie	Polyamide 6.6, heat stabilised (PA66HS)
Height (H) 1.2 mm	Flammability	UL 94 HB
	Foot Part	Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
Length (L) 150 mm	Height (H)	1.2 mm
	Length (L)	150 mm
Length (L2) 20 mm	Length (L2)	20 mm
Min.Tensile Strength 225 N	Min.Tensile Strength	225 N
Operating Temperature -40 °C to +105 °C	Operating Temperature	-40 °C to +105 °C
Package Content packed in bag	Package Content packed in	bag
Pack Cont. 500 pcs.	Pack Cont.	500 pcs.
ROHS compliant Yes	ROHS compliant	Yes
Stud Ø 5.0 mm	Stud Ø	5.0 mm
Thickness (T) 1.2 mm	Thickness (T)	1.2 mm
Variant Inside Serrated	Variant	Inside Serrated
Width (W) 4.6 mm	Width (W)	4.6 mm

RoHS