

Technical data sheet

Article number:
150-77950

T30RFT6



Product Group	2-piece fixing ties with fir tree, with disc, for round holes
Product Family	Fir tree parts FT6
Material	Polyamide 6.6, heat stabilised (PA66HS), Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
Colour	Black (BK)
Application Tool	MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP
Bundle Ø max.	30.0 mm
Bundle Ø min.	3.0 mm
Cable Tie	Polyamide 6.6, heat stabilised (PA66HS)
CE Certification	No
Fixation Method	Fir Tree
Flammability	UL 94 HB
Foot Part	Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
for Hole Ø (FH)	6.4 - 7.1 mm
Height (H)	1.1 mm
Length (L)	150.0 mm
Length (L2)	11.7 mm
Min.Tensile Strength	135 N
Operating Temperature	-40 °C to +105 °C
Package Content packed in	pcs.
Pack Cont.	500 pcs.
Panel Thickness	3.0 mm
Panel Thickness max.	0.75 - 3.0 mm
Panel Thickness min. (metric)	0.75 mm
ROHS compliant	Yes
Variant	Inside Serrated
Width (W)	3.5 mm



