

Technical data sheet

Article number:
151-01306

LOC5-9FTOVAL

| | |
|--------------------------------------|---|
| Product Group | Fixing Elements for Tubes and Pipes |
| Product Family | LOC-Series |
| Material | Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV) |
| Colour | Black (BK) |
| | |
| Bundle Ø max. | 9.0 mm |
| Bundle Ø min. | 5.0 mm |
| CE Certification | No |
| Fixation Method | Fir Tree |
| Flammability | UL 94 HB |
| for Hole Ø (FH) | 6.2 x 12.2 mm, 6.5 x 12.5 mm, 6.5 x 13.0 mm, 7.0 x 12.0 mm |
| Height (H) | 34.2 mm |
| Length (L) | 25.5 mm |
| Min.Tensile Strength | 110 N |
| Operating Temperature | -40 °C to +105 °C |
| Package Content packed in | pack |
| Pack Cont. | 1700 pcs. |
| Panel Thickness | 6.75 mm |
| Panel Thickness max. | 0.6 - 6.75 mm |
| Panel Thickness min. (metric) | 0.6 mm |
| ROHS compliant | Yes |
| Width (W) | 12.0 mm |

