

## Materiale datablad

Varenummer  
151-01663

RCD180LM6



|                                |                                                                                                             |
|--------------------------------|-------------------------------------------------------------------------------------------------------------|
| <b>Produktgruppe</b>           | Ratchet P-Clamp                                                                                             |
| <b>Produktserie</b>            | Til bundtdiameter fra 36,0 mm op til 51,0 mm, D serien                                                      |
| <b>Materiale</b>               | Polyamid 6.6 slag- og varmebestandig modificeret, UV-stabiliseret (PA66HIRHSUV), Stål (ST), Zinkbelagt (ZN) |
| <b>Farve</b>                   | Sort (BK)                                                                                                   |
| <b>Antal pr.</b>               | pakke                                                                                                       |
| <b>Bredde (W)</b>              | 34,9 mm                                                                                                     |
| <b>Bundtdiameter max.</b>      | 51,0 mm                                                                                                     |
| <b>Bundtdiameter min.</b>      | 36,0 mm                                                                                                     |
| <b>CE certificering</b>        | Nej                                                                                                         |
| <b>Driftstemperatur</b>        | -40 °C til +105 °C                                                                                          |
| <b>Fikseringsmetode</b>        | Skrue montage                                                                                               |
| <b>Flammehæmmende egenskab</b> | Iht. UL94 HB                                                                                                |
| <b>Hul diameter (D)</b>        | 6.5 mm                                                                                                      |
| <b>Længde (L)</b>              | 232,5 mm                                                                                                    |
| <b>Længde (L2)</b>             | 166,5 mm                                                                                                    |
| <b>Min. trækstyrke</b>         | 445 N                                                                                                       |
| <b>Pakkeindhold</b>            | 140 Stk.                                                                                                    |
| <b>ROHS overensstemmelse</b>   | Ja                                                                                                          |
| <b>UL fil nummer</b>           | E64139                                                                                                      |
| <b>Variant</b>                 | Lang                                                                                                        |

