


## Technical data sheet

Article number:  
151-03146

RCD30SM8SS



|                                  |                                                        |
|----------------------------------|--------------------------------------------------------|
| <b>Product Group</b>             | Ratchet P-Clamp                                        |
| <b>Product Family</b>            | For bundle diameters from 36.0 mm to 51.0 mm, D-Series |
| <b>Material</b>                  | Polyamide 6.6/6, V0 (PA666V0), Stainless Steel (SS304) |
| <b>Colour</b>                    | Black (BK)                                             |
| <b>Bundle Ø max.</b>             | 51.0 mm                                                |
| <b>Bundle Ø min.</b>             | 36.0 mm                                                |
| <b>CE Certification</b>          | No                                                     |
| <b>Fixation Method</b>           | Screw Mounting                                         |
| <b>Flammability</b>              | UL 94 V0                                               |
| <b>for Hole Ø (FH)</b>           | 8.31 mm                                                |
| <b>Length (L)</b>                | 178.8 mm                                               |
| <b>Length (L2)</b>               | 95.0 mm                                                |
| <b>Min.Tensile Strength</b>      | 445 N                                                  |
| <b>Operating Temperature</b>     | -40 °C to +120 °C                                      |
| <b>Package Content packed in</b> | pack                                                   |
| <b>Pack Cont.</b>                | 160 pcs.                                               |
| <b>ROHS compliant</b>            | Yes                                                    |
| <b>Specifications</b>            | EN 45545-2                                             |
| <b>Variant</b>                   | Short                                                  |
| <b>Width (W)</b>                 | 34.9 mm                                                |

HF ✓ LFH ✓ RoHS ✓

EN 45545-2