

## Technical data sheet

Article number:  
151-04076

**SGROC15.5-20FTOVAL**

|                                      |                                                                                                          |
|--------------------------------------|----------------------------------------------------------------------------------------------------------|
| <b>Product Group</b>                 | Ratchet O-Clamp                                                                                          |
| <b>Material</b>                      | Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV), Thermoplastic Elastomer (TPE) |
| <b>Colour</b>                        | Black (BK)                                                                                               |
| <b>Bundle Ø max.</b>                 | 20.0 mm                                                                                                  |
| <b>Bundle Ø min.</b>                 | 15.5 mm                                                                                                  |
| <b>CE Certification</b>              | No                                                                                                       |
| <b>Fixation Method</b>               | Fir Tree                                                                                                 |
| <b>Flammability</b>                  | UL 94 HB                                                                                                 |
| <b>for Hole Ø (FH)</b>               | 6.2 x 12.2 mm, 6.5 x 12.5 mm, 6.5 x 13.0 mm, 7.0 x 12.0 mm                                               |
| <b>Height (H)</b>                    | 58.9 mm                                                                                                  |
| <b>Length (L)</b>                    | 58.1 mm                                                                                                  |
| <b>Min.Tensile Strength</b>          | 445 N                                                                                                    |
| <b>Operating Temperature</b>         | -40 °C to +105 °C                                                                                        |
| <b>Package Content packed in</b>     | carton                                                                                                   |
| <b>Pack Cont.</b>                    | 1000 pcs.                                                                                                |
| <b>Panel Thickness</b>               | 6.75 mm                                                                                                  |
| <b>Panel Thickness max.</b>          | 0.6 - 6.75 mm                                                                                            |
| <b>Panel Thickness min. (metric)</b> | 0.6 mm                                                                                                   |
| <b>ROHS compliant</b>                | Yes                                                                                                      |
| <b>Width (W)</b>                     | 20.5 mm                                                                                                  |

HF ✓

RoHS ✓