

## Technical data sheet

**Article number:**  
**151-14313**

**CTC7.5FT6LG**

|                                      |  |
|--------------------------------------|--|
| <b>Product Group</b>                 | Fixing elements for corrugated tubing, with fir tree             |
| <b>Product Family</b>                | CTC-Series   |
| <b>Material</b>                      | Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS) |
| <b>Colour</b>                        | Black (BK)   |
| <b>Fixation Method</b>               | Fir Tree   |
| <b>Flammability</b>                  | UL 94 HB   |
| <b>for Hole Ø (FH)</b>               | 6.5 - 7.0 mm   |
| <b>Height (H)</b>                    | 18.6 mm  |
| <b>Operating Temperature</b>         | -40 °C to +105 °C  |
| <b>Package Content packed in</b>     | bag  |
| <b>Pack Cont.</b>                    | 500 pcs.   |
| <b>Panel Thickness</b>               | 6.0 mm   |
| <b>Panel Thickness max.</b>          | 0.75 - 6.0 mm  |
| <b>Panel Thickness min. (metric)</b> | 0.75 mm  |
| <b>ROHS compliant</b>                | Yes  |
| <b>Width (W)</b>                     | 8.0 mm   |

**RoHS** 