


## Technical data sheet

Article number:  
155-46302

**T50SOSSB6HE**



|                                  |                                                                                                                        |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------|
| <b>Product Group</b>             | 1-Piece Fixing Ties for Weld , moveable                                                                                |
| <b>Material</b>                  | Polyamide 6.6, heat stabilised (PA66HS)                                                                                |
| <b>Colour</b>                    | Black (BK)                                                                                                             |
| <b>Application Tool</b>          | ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP |
| <b>Bundle Ø max.</b>             | 35.0 mm                                                                                                                |
| <b>Bundle Ø min.</b>             | 1.0 mm                                                                                                                 |
| <b>CE Certification</b>          | No                                                                                                                     |
| <b>Fixation Method</b>           | Stud Mount                                                                                                             |
| <b>Flammability</b>              | UL 94 V2                                                                                                               |
| <b>Length (L)</b>                | 160.0 mm                                                                                                               |
| <b>Min.Tensile Strength</b>      | 170 N                                                                                                                  |
| <b>Operating Temperature</b>     | -40 °C to +105 °C                                                                                                      |
| <b>Package Content packed in</b> | pack                                                                                                                   |
| <b>Pack Cont.</b>                | 500 pcs.                                                                                                               |
| <b>ROHS compliant</b>            | Yes                                                                                                                    |
| <b>Stud Ø</b>                    | 6.0 mm                                                                                                                 |
| <b>Thickness (T)</b>             | 1.35 mm                                                                                                                |
| <b>Variant</b>                   | Outside Serrated                                                                                                       |
| <b>Width (W)</b>                 | 4.7 mm                                                                                                                 |

