


Technical data sheet

Article number:

Product Group

156-00057 T30RFT7



Product Family	Fir tree parts FT7
Material	Polyamide 6.6, heat stabilised (PA66HS)
Colour	Black (BK)
Application Tool	MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP
Bundle Ø max.	35.0 mm
Bundle Ø min.	4.0 mm
Cable Tie	Polyamide 6.6, heat stabilised (PA66HS)
CE Certification	No
Fixation Method	Fir tree for round holes
Flammability	UL 94 V2
Foot Part	Polyamide 6.6, heat stabilised (PA66HS)
for Hole Ø (FH)	6.5 - 7.0 mm
Height (H)	1.1 mm
Length (L)	150.0 mm
Length (L2)	11.6 mm
Min.Tensile Strength	135 N
Operating Temperature	-40 °C to +105 °C
Package Content packed in	pack
Pack Cont.	500 pcs.
Panel Thickness	7.0 mm
Panel Thickness max.	0.8 - 7.0 mm
Panel Thickness min. (metric)	0.8 mm
ROHS compliant	Yes
Thickness (T)	1.1 mm
Variant	Inside Serrated
Width (W)	3.5 mm

2-piece fixing ties with fir tree, with disc, for round holes

