

Technical data sheet

Article number:
156-00065

T50LFT10



Product Group	2-piece fixing ties with fir tree, with disc, for round holes
Product Family	Fir tree parts FT10
Material	Polyamide 6.6, heat stabilised (PA66HS)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP
Bundle Ø max.	106.0 mm
Bundle Ø min.	4.0 mm
Cable Tie	Polyamide 6.6, heat stabilised (PA66HS)
Fixation Method	Fir Tree
Flammability	UL 94 V2
Foot Part	Polyamide 6.6, heat stabilised (PA66HS)
for Hole Ø (FH)	9.7 - 10.0 mm
Height (H)	1.2 mm
Length (L)	390.0 mm
Length (L2)	12 mm
Min.Tensile Strength	225 N
Operating Temperature	-40 °C to +105 °C
Package Content packed in	bag
Pack Cont.	500 pcs.
Panel Thickness	5.0 mm
Panel Thickness min. (metric)	0.8 mm
ROHS compliant	Yes
Thickness (T)	1.2 mm
Variant	Inside Serrated
Width (W)	4.6 mm

