

Technical data sheet

Article number:
156-00066

T50LFT6



Product Group	2-piece fixing ties with fir tree, with disc, for round holes
Product Family	Fir tree parts FT6
Material	Polyamide 6.6, heat stabilised (PA66HS), Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP
Bundle Ø max.	110.0 mm
Bundle Ø min.	4.0 mm
Cable Tie	Polyamide 6.6, heat stabilised (PA66HS)
CE Certification	No
Fixation Method	Fir tree for round holes
Flammability	UL 94 V2
Foot Part	Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
for Hole Ø (FH)	6.4 - 7.1 mm
Height (H)	1.2 mm
Length (L)	390.0 mm
Length (L2)	11.6 mm
Min.Tensile Strength	225 N
Operating Temperature	-40 °C to +105 °C
Package Content packed in	pack
Pack Cont.	500 pcs.
Panel Thickness	3.0 mm
Panel Thickness max.	0.75 - 3.0 mm
Panel Thickness min. (metric)	0.75 mm
ROHS compliant	Yes

Thickness (T)	1.2 mm
Variant	Inside Serrated
Width (W)	4.6 mm

