

Technical data sheet

Article number:
156-00068

WSSFT9A



Product Group	2-piece fixing ties with fir tree, with disc, for round holes
Product Family	Fir tree parts FT9
Material	Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, MK9P, MK9P w/ Upper air, MK21, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9HT, EVO9i, EVO9iHT
Bundle Ø max.	57.0 mm
Cable Tie	Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV)
CE Certification	No
Fixation Method	Fir tree for round holes
Flammability	UL 94 HB
Foot Part	Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV)
for Hole Ø (FH)	8.7 - 9.2 mm
Height (H)	19.10 mm
Length (L)	228.0 mm
Min.Tensile Strength	535 N
Operating Temperature	-40 °C to +105 °C
Package Content packed in	pack
Pack Cont.	100 pcs.
Panel Thickness	6.5 mm
Panel Thickness max.	1.0 - 6.5 mm
Panel Thickness min. (metric)	1.0 mm
ROHS compliant	Yes
Variant	Inside Serrated
Width (W)	12.7 mm

