


Technical data sheet

Article number:

Product Group

156-00071 T120RFT9B



Product Family	Fir tree parts FT9
Material	Polyamide 6.6, heat stabilised (PA66HS), Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT
Bundle Ø max.	105.0 mm
Bundle Ø min.	5.0 mm
Cable Tie	Polyamide 6.6, heat stabilised (PA66HS)
CE Certification	No
Fixation Method	Fir tree for round holes
Flammability	UL 94 HB
Foot Part	Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV)
for Hole Ø (FH)	8.7 - 9.2 mm
Height (H)	28.5 mm
Length (L)	380.0 mm
Length (L2)	22.6 mm
Min.Tensile Strength	535 N
Operating Temperature	-40 °C to +105 °C
Package Content packed in	pack
Pack Cont.	100 pcs.
Panel Thickness	15.8 mm
Panel Thickness max.	1.0 - 15.8 mm
Panel Thickness min. (metric)	1.0 mm
ROHS compliant	Yes

2-piece fixing ties with fir tree, with disc, for round holes



Thickness (T)	1.8 mm
Variant	Inside Serrated
Width (W)	7.6 mm

RoHS