


Technical data sheet

Article number:
156-00076

T50ROSFT6



Product Group	2-piece fixing ties with fir tree, with disc, for round holes
Product Family	Fir tree parts FT6
Material	Polyamide 6.6, heat stabilised (PA66HS), Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP
Bundle Ø max.	45.0 mm
Bundle Ø min.	4.0 mm
Cable Tie	Polyamide 6.6, heat stabilised (PA66HS)
Fixation Method	Fir Tree
Flammability	UL 94 HB
Foot Part	Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
for Hole Ø (FH)	6.4 - 7.1 mm
Height (H)	1.3 mm
Length (L)	200 mm
Length (L2)	11.6 mm
Min.Tensile Strength	225 N
Operating Temperature	-40 °C to +105 °C
Package Content packed in	pcs.
Pack Cont.	500 pcs.
Panel Thickness	3.0 mm
Panel Thickness min. (metric)	0.75 mm
ROHS compliant	Yes
Thickness (T)	1.3 mm
Variant	Outside Serrated
Width (W)	4.6 mm



