

Technical data sheet

Article number:
156-00093

T50LFT10



Product Group	2-piece fixing ties with fir tree, with disc, for round holes
Product Family	Fir tree parts FT10
Material	Polyamide 6.6, heat stabilised (PA66HS), Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP
Bundle Ø max.	110.0 mm
Bundle Ø min.	4.0 mm
CE Certification	No
Fixation Method	Fir tree for round holes
Flammability	UL 94 HB
for Hole Ø (FH)	9.7 - 10.0 mm
Height (H)	1.20 mm
Length (L)	380.0 mm
Length (L2)	12.0 mm
Min.Tensile Strength	225 N
Operating Temperature	-40 °C to +105 °C
Package Content packed in	pack
Pack Cont.	500 pcs.
Panel Thickness	5.0 mm
Panel Thickness max.	0.8 - 5.0 mm
Panel Thickness min. (metric)	0.8 mm
ROHS compliant	Yes
Variant	Inside Serrated
Width (W)	4.7 mm

