HellermannTyton

Technical data sheet

Article number: 156-00338

T18RFT3

•	L	

Product Group	2-piece fixing ties with fir tree, with disc, for round holes
Product Family	Fir tree parts FT3
Material	Polyamide 6.6, heat and UV-stabilised (PA66HSUV)
Colour	Black (BK)

Application Tool	MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP
Bundle Ø max.	20.0 mm
Cable Tie	Polyamide 6.6, heat and UV-stabilised (PA66HSUV)
Fixation Method	Fir Tree
Flammability	UL 94 V2
Foot Part	Polyamide 6.6, heat and UV-resistant (PA66HSW)
for Hole Ø (FH)	M3
Length (L)	100.0 mm
Length (L2)	10.2 mm
Min.Tensile Strength	80 N
Operating Temperature	-40 °C to +110 °C
Package Content packed in	bag
Pack Cont.	100 pcs.
Panel Thickness	3.0 mm
Panel Thickness min. (metric)	1.5 mm
ROHS compliant	Yes
Thickness (T)	1.1 mm
Variant	Inside Serrated
Width (W)	2.5 mm

RoHS