


## **Technical data sheet**

**Article number:** 

**Product Group** 

156-00343 T50RFT5



| Product Family                | Fir tree parts FT5   |
|-------------------------------|--|
| Material                      | Polyamide 6.6, heat and UV-stabilised (PA66HSUV), Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)     |
| Colour                        | Black (BK)   |
|                               |  |
| Application Tool              | ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP |
| Bundle Ø max.                 | 45.0 mm  |
| Bundle Ø min.                 | 4.0 mm   |
| Fixation Method               | Fir Tree   |
| Flammability                  | UL 94 HB   |
| for Hole Ø (FH)               | 4.5 - 5.0 mm, M6   |
| Height (H)                    | 1.2 mm   |
| Length (L)                    | 202 mm   |
| Length (L2)                   | 13.2 mm  |
| Min.Tensile Strength          | 225 N  |
| Operating Temperature         | -40 °C to +105 °C  |
| Package Content packed in     | bag  |
| Pack Cont.                    | 100 pcs.   |
| Panel Thickness               | 3.00 mm  |
| Panel Thickness min. (metric) | 0.70 mm  |
| ROHS compliant                | Yes  |
| Thickness (T)                 | 1.2 mm   |
| Variant                       | Inside Serrated  |
| Width (W)                     | 4.6 mm   |
|                               |  |

2-piece fixing ties with fir tree, with disc, for round holes

