


Technical data sheet

Article number:
156-00344

T50RFT6



Product Group	2-piece fixing ties with fir tree, with disc, for round holes
Product Family	Fir tree parts FT6
Material	Polyamide 6.6, heat and UV-stabilised (PA66HSUV), Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP
Bundle Ø max.	45.0 mm
Bundle Ø min.	4.0 mm
Fixation Method	Fir Tree
Flammability	UL 94 HB
for Hole Ø (FH)	6.4 - 7.1 mm, M8
Length (L)	202 mm
Length (L2)	13.8 mm
Min.Tensile Strength	225 N
Operating Temperature	-40 °C to +105 °C
Package Content packed in	bag
Pack Cont.	100 pcs.
Panel Thickness	3.00 mm
Panel Thickness min. (metric)	0.75 mm
ROHS compliant	Yes
Thickness (T)	1.2 mm
Variant	Inside Serrated
Width (W)	4.6 mm

