

Technical data sheet

Article number:
156-00346

T50RFT8



Product Group	2-piece fixing ties with fir tree, with disc, for round holes
Product Family	Fir tree parts FT8
Material	Polyamide 6.6, heat and UV-stabilised (PA66HSUV), Polyamide 6.6, heat stabilised (PA66HS)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP
Bundle Ø max.	45.0 mm
Bundle Ø min.	5.0 mm
Cable Tie	Polyamide 6.6, heat and UV-stabilised (PA66HSUV)
Fixation Method	Fir Tree
Flammability	UL 94 V2
for Hole Ø (FH)	7.7 - 8.0 mm
Height (H)	1.2 mm
Length (L)	202 mm
Length (L2)	17.4 mm
Min.Tensile Strength	225 N
Mounting Screw Type	Plated through hole
Operating Temperature	-40 °C to +105 °C
Package Content packed in	bag
Pack Cont.	100 pcs.
Panel Thickness	6.00 mm
Panel Thickness min. (metric)	0.80 mm
ROHS compliant	Yes
Thickness (T)	1.2 mm
Variant	Inside Serrated
Width (W)	4.6 mm

