

Technical data sheet

Article number:
156-00348

T50LFT7



Product Group	2-piece fixing ties with fir tree, with disc, for round holes
Product Family	Fir tree parts FT7
Material	Polyamide 6.6, heat and UV-stabilised (PA66HSUV), Polyamide 6.6, heat stabilised (PA66HS)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP
Bundle Ø max.	100 mm
Bundle Ø min.	4.0 mm
Fixation Method	Fir Tree
Flammability	UL 94 V2
for Hole Ø (FH)	6.5 - 7.0 mm, M8
Height (H)	1.2 mm
Length (L)	383 mm
Length (L2)	18.9 mm
Min.Tensile Strength	225 N
Operating Temperature	-40 °C to +105 °C
Package Content packed in	bag
Pack Cont.	50 pcs.
Panel Thickness	7.00 mm
Panel Thickness min. (metric)	0.80 mm
ROHS compliant	Yes
Thickness (T)	1.5 mm
Variant	Inside Serrated
Width (W)	4.8 mm

