

## **Technical data sheet**

Article number:

**Product Group** 

156-00377 T50IFT8



Product Family	Fir tree parts FT8
Material	Polyamide 6.6, heat stabilised (PA66HS)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP
Bundle Ø max.	81.0 mm
Bundle Ø min.	4.0 mm
Cable Tie	Polyamide 6.6, heat stabilised (PA66HS)
CE Certification	No
Fixation Method	Fir tree for round holes
Flammability	UL 94 V2
Foot Part	Polyamide 6.6, heat stabilised (PA66HS)
for Hole Ø (FH)	7.7 - 8.0 mm
Height (H)	1.20 mm
Length (L)	305.0 mm
Length (L2)	12.0 mm
Min.Tensile Strength	225 N
Operating Temperature	-40 °C to +105 °C
Package Content packed in	pack
Pack Cont.	500 pcs.
Panel Thickness	5.0 mm
Panel Thickness max.	0.8 - 5.0 mm
Panel Thickness min. (metric)	0.8 mm
ROHS compliant	Yes
Variant	Inside Serrated
Width (W)	4.6 mm

2-piece fixing ties with fir tree, with disc, for round holes

