

## Technical data sheet

Article number:  
156-00406

**T120RHDM6**

<b>Product Group</b>	2-Piece Fixing Ties for Heavy Duty Applications, for Screws or Bolts
<b>Product Family</b>	HDM-Series
<b>Material</b>	Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
<b>Colour</b>	Black (BK)
<b>Application Tool</b>	ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT
<b>Bundle Ø max.</b>	105.0 mm
<b>Bundle Ø min.</b>	15.0 mm
<b>Cable Tie</b>	Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
<b>CE Certification</b>	No
<b>Fixation Method</b>	Screw Mount
<b>Flammability</b>	UL 94 HB
<b>Foot Part</b>	Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
<b>for Hole Ø (FH)</b>	6.2 mm
<b>Height (H)</b>	16.0 mm
<b>Length (L)</b>	390.0 mm
<b>Length (L2)</b>	37.5 mm
<b>Min.Tensile Strength</b>	535 N
<b>Mounting Screw Type</b>	M6 Screw
<b>Operating Temperature</b>	-40 °C to +110 °C
<b>Package Content packed in</b>	pack
<b>Pack Cont.</b>	100 pcs.
<b>ROHS compliant</b>	Yes
<b>Thickness (T)</b>	1.8 mm
<b>Variant</b>	Inside Serrated
<b>Width (W)</b>	7.6 mm

