

Technical data sheet

Article number:
156-00455

T50ROSP1SFT6.5

Product Group	2-Piece Fixing Ties with Arrowhead, with Disc, for high temperature applications
Product Family	T50ROSP1SFT6.5 for panel thickness 0.7 - 1.3 mm
Material	Polyamide 4.6 (PA46), Polyetheretherketone (PEEK)
Colour	Grey (GY), Beige (BGE)
Application Tool	ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP
Bundle Ø max.	45.0 mm
Bundle Ø min.	1.0 mm
Cable Tie	Polyamide 4.6 (PA46)
Fixation Method	arrowhead
Flammability	UL 94 V2
Foot Part	Polyetheretherketone (PEEK)
for Hole Ø (FH)	6.3 - 6.7 mm
Height (H)	15.0 mm
Length (L)	200.0 mm
Length (L2)	8.6 mm
Min.Tensile Strength	225 N
Operating Temperature	-40 °C to +130 °C, -55 °C to +240 °C
Package Content packed in	bag
Pack Cont.	100 pcs.
Panel Thickness	1.3 mm
Panel Thickness max.	0.7 – 1.3 mm
Panel Thickness min. (metric)	0.7 mm
ROHS compliant	Yes
Thickness (T)	1.3 mm
Variant	Outside Serrated
Width (W)	4.6 mm

