

## Technical data sheet

Article number:  
156-00588

**T50REC4B**

|                               |                                                                                                                        |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------|
| Product Group                 | 2-piece fixing ties for edges                                                                                          |
| Product Family                | EdgeClip-Series, 1.0 - 3.0 mm, top fixing                                                                              |
| Material                      | Polyamide 6.6, UV-stabilised (PA66UV), Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)                |
| Colour                        | Black (BK)                                                                                                             |
| Application Tool              | ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP |
| Bundle Ø max.                 | 45.0 mm                                                                                                                |
| Bundle Ø min.                 | 4.0 mm                                                                                                                 |
| Cable Tie                     | Polyamide 6.6, UV-stabilised (PA66UV)                                                                                  |
| CE Certification              | No                                                                                                                     |
| Fixation Method               | Edge Clip                                                                                                              |
| Flammability                  | UL 94 HB                                                                                                               |
| Foot Part                     | Polyamide 6.6, high impact modified, heat and UV-resistant (PA66HIRHSW)                                                |
| Height (H)                    | 16.0 mm                                                                                                                |
| Length (L)                    | 202.0 mm                                                                                                               |
| Length (L2)                   | 14.0 mm                                                                                                                |
| Min.Tensile Strength          | 225 N                                                                                                                  |
| Operating Temperature         | -40 °C to +125 °C, -40 °C to +105 °C                                                                                   |
| Package Content packed in     | pack                                                                                                                   |
| Pack Cont.                    | 100 pcs.                                                                                                               |
| Panel Thickness               | 3.0 mm                                                                                                                 |
| Panel Thickness max.          | 1.0 - 3.0 mm                                                                                                           |
| Panel Thickness min. (metric) | 1.0 mm                                                                                                                 |
| ROHS compliant                | Yes                                                                                                                    |
| Thickness (T)                 | 1.2 mm                                                                                                                 |
| Variant                       | Inside Serrated                                                                                                        |
| Width (W)                     | 4.6 mm                                                                                                                 |

