


## **Technical data sheet**

Article number: 156-00619

**Product Group** 

**T50RFT8** 



Product Family	Fir tree parts FT8
Material	Polyamide 6.6, heat stabilised (PA66HS), Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP
Bundle Ø max.	45.0 mm
Bundle Ø min.	5.0 mm
Cable Tie	Polyamide 6.6, heat stabilised (PA66HS)
Fixation Method	Fir Tree
Flammability	UL 94 V2
for Hole Ø (FH)	7.7 - 8.0 mm
Height (H)	1.2 mm
Length (L)	200.0 mm
Length (L2)	12.0 mm
Min.Tensile Strength	225 N
Package Content packed in	bag
Pack Cont.	250 pcs.
Panel Thickness	6.0 mm
Panel Thickness min. (metric)	0.8 mm
ROHS compliant	Yes
Thickness (T)	1.2 mm
Variant	Inside Serrated
Width (W)	4.6 mm

2-piece fixing ties with fir tree, with disc, for round holes

