


Technical data sheet

Article number: 156-00625

Product Group

T50ROSFT6SD



	=
Product Family	Fir tree parts FT6
Material	Polyamide 6.6, heat stabilised (PA66HS), Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP
Bundle Ø max.	46.0 mm
Bundle Ø min.	1.0 mm
Cable Tie	Polyamide 6.6, heat stabilised (PA66HS)
Fixation Method	Fir Tree
Flammability	UL 94 HB
Foot Part	Polyamide 6.6, high impact modified (PA66HIR)
for Hole Ø (FH)	6.4 - 7.1 mm
Height (H)	1.3 mm
Length (L)	200 mm
Length (L2)	11.6 mm
Min.Tensile Strength	225 N
Operating Temperature	-40 °C to +80 °C
Package Content packed in	bag
Pack Cont.	500 pcs.
Panel Thickness	3.00 mm
Panel Thickness min. (metric)	0.75 mm
ROHS compliant	Yes
Variant	Outside Serrated
Width (W)	4.6 mm
· · · · · · · · · · · · · · · · · · ·	

2-piece fixing ties with fir tree, with disc, for round holes

RoHS