


## **Technical data sheet**

Article number: 156-00724

**T30RFT7** 



| Product Group                 | 2-piece fixing ties with fir tree, with disc, for round holes       |
|-------------------------------|---------------------------------------------------------------------|
| Product Family                | Fir tree parts FT7                                                  |
| Material                      | Polyamide 6.6 (PA66)                                                |
| Colour                        | Natural (NA), Black (BK)                                            |
|                               |                                                                     |
| Application Tool              | MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP |
| Bundle Ø max.                 | 30.0 mm                                                             |
| Bundle Ø min.                 | 4.0 mm                                                              |
| Cable Tie                     | Polyamide 6.6 (PA66)                                                |
| Fixation Method               | Fir Tree                                                            |
| Flammability                  | UL 94 V2                                                            |
| Foot Part                     | Polyamide 6.6 (PA66)                                                |
| for Hole Ø (FH)               | 6.5 - 7.0 mm                                                        |
| Height (H)                    | 1.1 mm                                                              |
| Length (L)                    | 148 mm                                                              |
| Min.Tensile Strength          | 135 N                                                               |
| Operating Temperature         | -40 °C to +85 °C                                                    |
| Package Content packed in     | bag                                                                 |
| Pack Cont.                    | 200 pcs.                                                            |
| Panel Thickness               | 7.00 mm                                                             |
| Panel Thickness min. (metric) | 0.80 mm                                                             |
| ROHS compliant                | Yes                                                                 |
| Thickness (T)                 | 1.2 mm                                                              |
| Variant                       | Inside Serrated                                                     |
| Width (W)                     | 3.6 mm                                                              |

