

## Technical data sheet

Article number:  
156-00815

**T80ISBH5**

|                                  |                                                                                                              |
|----------------------------------|--------------------------------------------------------------------------------------------------------------|
| <b>Product Group</b>             | 2-Piece Fixing Ties for Weld Studs, with Plate (for isolation material)                                      |
| <b>Material</b>                  | Polyamide 6.6, heat stabilised (PA66HS)                                                                      |
| <b>Colour</b>                    | Black (BK)                                                                                                   |
| <b>Application Tool</b>          | ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT |
| <b>Bundle Ø max.</b>             | 80.0 mm                                                                                                      |
| <b>Bundle Ø min.</b>             | 8.0 mm                                                                                                       |
| <b>Cable Tie</b>                 | Polyamide 6.6, heat stabilised (PA66HS)                                                                      |
| <b>Fixation Method</b>           | Weld Stud Fixing                                                                                             |
| <b>Flammability</b>              | UL 94 V2                                                                                                     |
| <b>Foot Part</b>                 | Polyamide 6.6, heat stabilised (PA66HS)                                                                      |
| <b>Height (H)</b>                | 1.3 mm                                                                                                       |
| <b>Length (L)</b>                | 300 mm                                                                                                       |
| <b>Length (L2)</b>               | 12 mm                                                                                                        |
| <b>Min.Tensile Strength</b>      | 355 N                                                                                                        |
| <b>Operating Temperature</b>     | -40 °C to +105 °C                                                                                            |
| <b>Package Content packed in</b> | bag                                                                                                          |
| <b>Pack Cont.</b>                | 500 pcs.                                                                                                     |
| <b>ROHS compliant</b>            | Yes                                                                                                          |
| <b>Stud Ø</b>                    | 5.0 mm                                                                                                       |
| <b>Thickness (T)</b>             | 1.3 mm                                                                                                       |
| <b>Variant</b>                   | Inside Serrated                                                                                              |
| <b>Width (W)</b>                 | 5.0 mm                                                                                                       |

