


Technical data sheet

Article number: 156-00921

Product Group

T30LFT6LG



Product Family	Fir tree parts FT6
Material	Polyamide 6.6, heat stabilised (PA66HS), Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
Colour	Black (BK)
Application Tool	MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP
Bundle Ø max.	50.0 mm
Bundle Ø min.	5.0 mm
Cable Tie	Polyamide 6.6, heat stabilised (PA66HS)
Fixation Method	Fir Tree
Flammability	UL 94 HB
Foot Part	Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
for Hole Ø (FH)	6.4 - 7.1 mm
Height (H)	1.2 mm
Length (L)	200 mm
Length (L2)	11.6 mm
Min.Tensile Strength	133 N
Operating Temperature	-40 °C to +105 °C
Package Content packed in	bag
Pack Cont.	500 pcs.
Panel Thickness	6.00 mm
Panel Thickness min. (metric)	0.75 mm
ROHS compliant	Yes
Variant	Inside Serrated
Width (W)	3.5 mm

2-piece fixing ties with fir tree, with disc, for round holes

