


Technical data sheet

Article number:

Product Group

156-00953 T30RFT4



Product Family	Fir tree parts FT4
Material	Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV), Polyamide 6.6, heat stabilised (PA66HS)
Colour	Black (BK)
Application Tool	MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP
Bundle Ø max.	35.0 mm
Bundle Ø min.	1.5 mm
CE Certification	No
Fixation Method	Fir tree for round holes
for Hole Ø (FH)	3.3 - 4.0 mm
Height (H)	11.8 mm
Length (L)	148.0 mm
Min.Tensile Strength	135 N
Operating Temperature	-40 °C to +105 °C, (+135 °C, 200 h), -40 °C to +125 °C
Package Content packed in	pack
Pack Cont.	500 pcs.
Panel Thickness	3.0 mm
Panel Thickness max.	1.0 - 3.0 mm
Panel Thickness min. (metric)	1.0 mm
ROHS compliant	Yes
Variant	Inside Serrated
Width (W)	3.6 mm

2-Pieces Fixing Ties with Fir Tree, with Disc, for Round Holes

RoHS